

ES-100VII 2 MHz

For Determination of Fetal Heart Rate (2 MHz probe only)



FETAL DOPPLER WITH ADVANCED LCD & SPEAKER

Displays real-time fetal heart rate with great sounds.

FREEZE KEY

Freezes heart rate for notation.

USEFUL INDICATORS

Heartbeat indicator tracks heartbeat.
LCD flashes when calculated heart rate is not stable.
Low battery indicator

EASY & SAFE TO OPERATE

Safe and effective low-intensity beam

WATERPROOF PROBE AVAILABLE

CLINICAL APPLICATIONS

- Detection of fetal heart sounds
- Determination and monitoring of fetal heart rate
- Verify fetal heart viability following patient trauma

DISPLAY SAMPLE



SPECIFICATIONS

Power:	DC9V, 9 V alkaline battery	Outputs:	Headset:	Speaker cut off
Heart rate range:	60 to 240 bpm	Dimensions:		102(W) x 142(D) x 27(H) mm
Automatic shut-off		Weight:		280 grams (including battery and probe)
Speaker output:	250 mW or more	Electrical safety:		Conform to IEC60601-1
Probe freq.:	2 MHz	Option:		Waterproof
Mode settings:	Freeze			
LCD display:	Heart rate, Low battery indicator			

* Specifications subject to change.

EXCELLENCE IN HUMAN SERVICE AND TECHNOLOGY



Hadeco, Inc.

Website: www.hadeco.co.jp/

Smart Nine, Corp.

Kawasaki, Japan

TEL +81-44-860-3901 FAX +81-44-856-0179



To order, or for more information, please contact;

docStock
com.au

Ph: (02) 8850 7177 Fax: (02) 8850 7988
email: info@docstock.com.au

www.docstock.com.au [...medical products online]